

| | RWC | 351 | 411 | 451 | 502 | 562 | 602 | 642 | 692 | 752 | 812 |
|---------------------------|-------|--------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | 346 | 405 | 445 | 502 | 558 | 602 | 644 | 690 | 758 | 806 |
| | | 56,3 | 68,0 | 78,5 | 88,4 | 100,4 | 107,6 | 106,0 | 114,2 | 127,6 | 138,2 |
| EER _{NET} | | 6,15 | 5,96 | 5,67 | 5,68 | 5,56 | 5,59 | 6,08 | 6,04 | 5,94 | 5,83 |
| ESEER (ARI ST 555/590-98) | | 8,14 | 7,90 | 7,51 | 7,57 | 7,41 | 7,45 | 7,87 | 7,82 | 7,67 | 7,55 |
| | | 402 | 473 | 524 | 590 | 658 | 710 | 750 | 804 | 886 | 944 |
| | nr. | 1 | | | | | | | | | |
| | nr. | 1 | | | | | 2 | | | | |
| | A | 97 | 115 | 131 | 144 | 162 | 176 | 182 | 195 | 216 | 232 |
| | nr. | 1 | | | | | | | | | |
| Water flow | 3/ | 59,4 | 69,5 | 76,4 | 86,2 | 95,8 | 103,3 | 110,6 | 118,5 | 130,1 | 138,4 |
| Pressure drop | | 54 | 42 | 48 | 46 | 55 | 48 | 52 | 38 | 48 | 54 |
| Water cooled condenser | nr. | 1 | | | | | | | | | |
| | 3/ | 69,1 | 81,2 | 89,9 | 101,4 | 113,0 | 121,8 | 128,8 | 138,1 | 152,0 | 162,1 |
| | | 61 | 82 | 82 | 84 | 62 | 72 | 79 | 63 | 76 | 86 |
| | dB(A) | 78 | 78 | 78 | 76 | 77 | 78 | 80 | 80 | 80 | 81 |
| | | 2 420 | | | | | 2 750 | | | | |
| | | 1 420 | | | | | 1 500 | | | | |
| | | 2 070 | | | | | | | | | |
| | | 1 780 | 1 810 | 1 930 | 2 665 | 2 730 | 2 840 | 2 895 | 2 950 | 3 065 | 3 065 |
| | | 400 V / 3 ph / 50 Hz + T | | | | | | | | | |

| | RWC | 863 | 923 | 983 | 1083 | 1183 | 1324 | 1494 | 1644 | 1804 | |
|---------------------------|-------|--------------------------|-------|-------|-------|-------|-------|-------|-------|-------|--|
| | | 870 | 920 | 985 | 1 080 | 1 180 | 1 326 | 1 496 | 1 640 | 1 800 | |
| | | 157,8 | 169,8 | 162,3 | 179,7 | 199,8 | 218,8 | 250,8 | 283,6 | 319,2 | |
| EER _{NET} | | 5,51 | 5,42 | 6,07 | 6,01 | 5,91 | 6,06 | 5,96 | 5,78 | 5,64 | |
| ESEER (ARI ST 555/590-98) | | 7,56 | 7,44 | 8,11 | 8,02 | 7,89 | 7,82 | 7,70 | 7,46 | 7,28 | |
| | | 1 028 | 1 090 | 1 147 | 1 260 | 1 380 | 1 545 | 1 747 | 1 924 | 2 119 | |
| | nr. | 1 | | | | | 2 | | | | |
| | nr. | 3 | | | | | 4 | | | | |
| | A | 254 | 272 | 278 | 305 | 336 | 375 | 424 | 475 | 537 | |
| | nr. | 1 | | | | | | | | | |
| Water flow | 3/ | 149,4 | 157,9 | 169,1 | 185,4 | 202,6 | 227,6 | 256,8 | 281,5 | 309,0 | |
| Pressure drop | | 32 | 32 | 38 | 42 | 48 | 34 | 42 | 49 | 51 | |
| Water cooled condenser | nr. | 1 | | | | | 2 | | | | |
| | 3/ | 176,4 | 187,1 | 197,0 | 216,3 | 236,9 | 265,2 | 299,9 | 330,2 | 363,8 | |
| | | 86 | 96 | 28 | 34 | 34 | 34 | 61 | 73 | 87 | |
| | dB(A) | 78 | 78 | 82 | 82 | 82 | 84 | 84 | 85 | 85 | |
| | | 3 550 | | | | | 4 420 | | | | |
| | | 1 600 | | | | | | | | | |
| | | 2 070 | | | | | | | | | |
| | | 4 250 | 4 250 | 4 415 | 4 465 | 4 540 | 5 120 | 5 230 | 5 230 | 5 395 | |
| | | 400 V / 3 ph / 50 Hz + T | | | | | | | | | |

- Operating conditions: evaporator water temperature 7/12°C; condenser water temperature 30/35°C
- Sound pressure level at 1 m in open field (ISO 3744).
- Unit weight including oil